

NitroCast® HE

Accelerating Admixture for Concrete

DESCRIPTION:

NitroCast® HE is a ready to use aqueous solution of calcium chloride and other proprietary accelerators which provides the benefits of improved finishability, set acceleration and high early strength gain.

NitroCast® HE enhances the performance of plastic and hardened concrete. **NitroCast® HE** is manufactured under rigid quality control measures to provide uniform, reliable results.

USES:

NitroCast® HE is recommended for concrete mixes where improved finishability, accelerated set and high early strengths are desirable.

ADVANTAGES:

- Improves workability, placeability and consolidation
- Improves finishability
- Accelerates cement hydration
- Reduces time to initial and final set
- Increases early compressive and flexural strengths

DOSAGE RATE:

NitroCast® HE is recommended for use at a dosage rate of 12 to 64 fluid ounces per 100 pounds (782 to 4170 ml per 100 kg) of cement. **NitroCast® HE** offers broad flexibility and dosage rates are dependent on cement quantity and chemistry, concrete temperature and curing conditions.

Because local job conditions vary, please contact your local Premiere Concrete Solutions Specialist for further assistance if using outside recommended dosage ranges.

SPECIFICATIONS:

Conforms to ASTM C 494 Type C

AASHTO M 194 Type C

CRD C 87 Type C



NitroCast® HE

COMPATIBILITY:

NitroCast® HE is compatible with all types of Portland cement, class C and F fly ash, slag, microsilica, fibers and approved water reducing and air entraining admixtures. For best results, each chemical admixture must be dispensed separately into the concrete mix.

STORAGE:

NitroCast® HE may freeze at temperatures below 5°F (2°C). Although freezing does not harm **NitroCast® HE**, precautions should be taken to protect it from freezing. If it should happen to freeze, thaw and reconstitute with mechanical agitation.

PACKAGING:

55-gallon drums and bulk deliveries.

Premiere Concrete Admixtures warrants its products to be free from defects in material and manufacture. There are no other warranties by Premiere Concrete Admixtures of any nature whatsoever, expressed or implied. This information is based on data and knowledge believed to be true and accurate at time of publication and is offered as a resource for the users of our products. Premiere Concrete Admixtures assumes no liability in the use of this information and does not warranty the results obtained for any application. Premiere Concrete Admixtures shall not be liable for damages of any sort, the use or results of this product and shall not be responsible for conditions outside its control, including but not limited to, other materials, design, inspection, workmanship and field conditions. No statement, recommendation, or other information is intended to infringe on any patent or copyright held by others.

