



PREMIERE  
CONCRETE  
SOLUTIONS



**FLO-L™**

PRODUCT DATA

## FLO-L – Flowable Fill Admixture

Low Strength Mortar Liquid Additive

### DESCRIPTION

**FLO-L – Flowable Fill Admixture** is an aqueous surfactant that produces flowable fill, also called controlled low strength material (CLSM), controlled density fill (CDF), or low strength mortar (LSM).

The use of **FLO-L – Flowable Fill Admixture** results in improved flowability while reducing the amount of mix water required to obtain a flowable mix. Reduces the subsidence normally associated with flowable fill mixes.

### USES

**FLO-L – Flowable Fill Admixture** greatly aids in completely filling the placement by flowing around structures and filling voids.

The use of **FLO-L – Flowable Fill Admixture** produces CLSM that is volume stable and shrinks less. It also is used to eliminate segregation, lower densities, and improve pumpability. The use of accelerating admixtures with **FLO-L – Flowable Fill Admixture** can allow for CLSM to be covered sooner to allow traffic and/or concrete placement.

### APPLICATIONS

- Street and highway cross cuttings
- Abandoned underground structures
- Utility excavations
- Backfill applications commercial and residential
- Pipe bedding
- Sub-grade base
- Backfill for radiant heat flatwork

### ADVANTAGES

- Produces an extremely fluid material with minimal subsidence
- Eliminates the costly need to backfill in lifts and compact between lifts
- Speeds up placement and results in significant savings of machine and man hours
- Produces stable volume with minimal segregation and bleed

### BATCHING

**FLO-L – Flowable Fill Admixture** can be added during or after the charging of the mixer. Mix for 5 minutes or 80 revolutions at mixing speed to assure adequate distribution.

### PACKAGING/DOSAGE

**FLO-L – Flowable Fill Admixture** is packaged in one-gallon, five-gallon and 55-gallon containers. Contact your Premiere Concrete Solutions Technical Sales representative for help in developing mixes that will work with raw materials.

### COMPATIBILITY

**FLO-L – Flowable Fill Admixture** is fully effective and compatible in concrete containing all types of Portland cement, class C and F fly ash, calcium chloride, fibers and approved water-reducing, accelerating and retarding admixtures.



PREMIERE CONCRETE SOLUTIONS  
P.O. Box 157 • 508 Cedar Street • Pioneer, Ohio 43554  
Phone: 800-503-3418 • Fax: 419-737-9400  
Email: support@premiereconcretesolutions.com  
Website www.bearcoat.net

**SHELF LIFE**

3 years

**TECHNICAL NOTE**

Please contact your PCS Technical Sales Representative for a pre-placement meeting to discuss helpful batching, placement, finishing and curing procedures.



*This Product is formulated and labeled for Industrial and Commercial Use only. For best results and safest usage, user is specifically directed to consult the current material safety data sheet and package label for this product.*

Premiere Concrete Solutions warrants its products to be free of manufacturing defects and that they will meet Premiere Concrete Solutions current published physical properties when applied in accordance with Premiere Concrete Solutions directions and tested in accordance with ASTM and Premiere Concrete Solutions standards. Premiere Concrete Solution makes no warranty or guarantee, express or implied, including warranties of fitness for a particular purpose or merchantability, respecting its products, and Premiere Concrete Solutions shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. Our liability shall be limited to replacement of, or refund of an amount not to exceed the purchase price attributed to, the goods as to which such claim is made. Our selection of one of these alternatives shall be Buyer's exclusive remedy. In no case shall we be liable for consequential or special damages. Even if we have been advised of the possibility of such damages. The foregoing warranties are in lieu of all other warranties, guarantees, co-conditions and representations, either expressed or implied, whether arising under any statute. Common Law, usage or trade, course of dealing or otherwise, including, but not limited to, the implied warranties of merchantability or fitness for a particular purpose. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith.

©2004 Premiere Concrete Solutions