

Date Prepared: 01/31/03
Supersedes: 4/16/02
Product Name: Ultimate

PREMIERE CONCRETE SOLUTIONS

Material Safety Data Sheet

1. Chemical Product and Company Information

Product Name: Ultimate

Product Description: Ultimate is a penetrating, chemically reactive alkylalkoxy silane moisture and water repellent for concrete and masonry.

Premiere Concrete Solutions

508 Cedar St
P.O. Box 157
Pioneer, Ohio 43554
Phone : 800-503-3418
Fax: 419-737-9400

In Case of Emergency Contact:

CHEMTREC 800-424-9300

2. Composition / Information on Ingredients

Hazardous Components	CAS#
Isooctyltrimethosylsilane	34396-03-7
Mineral Spirits As: Stoddard Solvent	8062-41-3
1,2,4 – Trimethylbenzene	95-63-6
1,3,5 – Trimethylbenzene	108-67-8

3. Hazards Identification

CAUTION

COMBUSTIBLE LIQUID

Causes eye, skin and lung irritation

Harmful if inhaled

Harmful if swallowed

Potential Health Hazards – ACUTE

Eye: Causes eye irritation. Direct contact with the liquid or exposure to its vapors may cause burning, tearing and redness.

Skin: May cause irritation. Prolonged or repeated exposure may cause redness and burning, drying and cracking of the skin and dermatitis. Persons with preexisting skin disorders may be more susceptible to the effects of this material.

Inhalation: Excessive concentrations of vapors or mists may cause irritation of the nose and throat and signs of nervous system depression. Persons with impaired lung function or asthma like conditions may experience additional breathing difficulties due to the irritating properties of this material.

Ingestion: Liquid is moderately toxic and may be harmful if swallowed; may produce CNS depression. May result in vomiting. Aspiration of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis.

Potential Health Effects – Chronic

Kidney, lung and liver are probable target organs. See Section 11 for further information.

Carcinogenicity: NTP	IARC Monographs	OSHA Regulated
NO	NO	NO

Date Prepared: 01/31/03
Supersedes: 4/16/02
Product Name: Ultimate

4. **First Aid Measures**

Eye: Immediately flush with plenty of clean water.

Skin: Remove contaminated clothing. Clean affected area(s) thoroughly with soap and water.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Ingestion: Seek medical attention! Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs.

SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST

5. **Fire Fighting Measures**

Flash Point (method used): 105⁰F (TCC)

Flammable Limits (% volume in air): Lower = 1 Upper = 6

Auto Ignition Temperature: No data available

Extinguishing Media: Extinguish with water fog, dry chemical, CO₂ or foam.

Hazard Combustion Products: Carbon dioxide, carbon monoxide

Fire Fighting Instructions: Do not enter confined fire space without full bunker gear including a positive pressure, NIOSH approved, self-contained breathing apparatus. Cool containers exposed to fire with water.

6. **Accidental Release Measures**

Spill: Shut off ignition sources. Absorb with inert material, and then place in chemical waste container for later disposal.

7. **Handling and Storage**

Handling: Avoid inhalation of vapors and personal contact with product. Keep liquid away from heat, sparks and flame. Use with adequate ventilation. "Empty" containers can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize drums to empty them.

Storage: Store containers tightly closed with adequate ventilation in a cool, dry area.

8. **Exposure Controls / Personal Protection**

Exposure Controls: Not Applicable – for outdoor use.

Personal Protection: Protective clothing, goggles, neoprene gloves and a vapor respirator when TLV is exceeded.

9. **Physical and Chemical Properties**

Appearance: Clear liquid of low viscosity

Odor: Mineral Spirits odor

VOC Content: 516 gm/L (4.3 lbs./gal)

Boiling Point: 300-390⁰F

Melting Point: Not applicable

Vapor Pressure (mm/Hg): 16 @ 100⁰F

Vapor Density (Air = 1): 4.8

Solubility in Water: Negligible (<5%)

Specific Gravity (H₂O = 1): 0.8

Evaporation Rate (n-Butyl Acetate =1): < 0.1*

- estimated

Date Prepared: 01/31/03
Supersedes: 4/16/02
Product Name: Ultimate

10. Stability and Reactivity

Chemical Stability: Stable

Conditions to Avoid: Heat, sparks and flame

Incompatibility (materials to avoid): Strong oxidizing agents.

Hazard Decomposition or By-products: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide.

Hazardous Polymerizations: Will not occur

11. Toxicological Information

Similar solvents when tested on rats by inhalation of vapors showed evidence of kidney, lung and liver damage.

Components	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Mineral Spirits	6 g/kg	3000 mg/kg	>5500 mg/m ³

12. Ecological Information

CWA considers petroleum distillates (mineral Spirits) an oil under Section 311. Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center.

13. Disposal Considerations

Dispose of in accordance with all federal, state, and local regulations. If uncertain of local requirements, contact the proper environmental authorities for information on waste disposal in your area. Under RCRA 40 CFR 261 this material is hazardous waste number D001.

14. Transportation Information

For U S National Shipments ≤ 119 gal containers: Not Regulated

For U S National Shipments > 119 gal containers:

Shipping Description: Resin Solution, Combustible Liquid, NA1866, III

Hazard Class: Combustible Liquid

For International, Vessel and Air Shipments: Resin Solution, 3, UN1866, III

Hazard Class: Flammable Liquid

Emergency Response Guide Number: 127

15. Regulatory Information

OSHA: This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910, 1200)

CERCLA Reportable Quantity: The CWA considers petroleum distillates (mineral spirits) an oil under Section 311. Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center.

Date Prepared: 01/31/03
Supersedes: 4/16/02
Product Name: Ultimate

SARA Title III:

Section 311/312 hazard categories: acute health, delayed health, fire

Section 313 reportable ingredients:

Components	CAS#	Maximum %
1,2,4 Trimethylbenzene	95-63-6	3%

16. Other Information

MSDS Status: Revised January 31, 2003
Industrial Abbreviation Legend listed below.

Industrial Abbreviation Legend

ACGIH	American Conference of Governmental Industrial Hygienists
CAA	Clean Air Act (EPA)
CERCLA	Comprehensive Environmental Response, Compensation & Liability Act of 1980 (Superfund)(EPA)
CNS	Central Nervous System
CWA	Clean Water Act (EPA)
DOT	Department of Transportation
EPA	Environmental Protection Agency
G/kg	grams per kilogram
IARC	Internal Agency for Research on Cancer
LC50	Lethal Concentration in which 50% of the test animals are expected to die
LD50	Lethal Dose in which 50% of the test animals are expected to die
Mg/m ³	milligrams per cubic meter
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
Ppm	parts per million
RCRA	Resource Conservation and Recovery Act (EPA)
SARA	EPA's Superfund Amendment and Reauthorization Act (EPA)
STEL	Short-Term Exposure Limit, ACGIH terminology
TLV	Threshold Limit Value
TWA	Time-Weighted Average

**THIS PRODUCT IS FORMULATED AND LABELED FOR
INDUSTRIAL AND COMMERCIAL APPLICATION ONLY**

The information contained herein is given in good faith and based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. The company assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.