

AccuCast™ SS455 Mortar Mix

DESCRIPTION:

AccuCast™ SS455 Mortar Mix is a specially formulated job-site added mortar admixture which reduces rain water penetration and efflorescence in mortar. **AccuCast™ SS455 Mortar Mix** will not adversely affect other properties such as board life or bond strength when used in conjunction with low permeability brick or water repellent concrete block produced with **AccuCast™ SS455**. Excellent water penetration resistance for the total masonry system can be obtained for ASTM E514 standard test method for water penetration and leakage through masonry. **AccuCast™ SS455 Mortar Mix** can be used in portland-lime or masonry cement mortars.

DIRECTIONS FOR USE:

Add AccuCast™ SS455 Mortar Mix to the mortar 30 seconds before final water and mix for five minutes to ensure a homogenous mixture.

CAUTION:

AccuCast™ SS455 Mortar Mix should not be added to mortar if ambient temperature is less than 34°F. **AccuCast™ SS455 Mortar Mix** should be protected from freezing. If **AccuCast™ SS455 Mortar Mix** does become frozen, DO NOT USE without manufacturer's approval.

PACKAGING:

AccuCast™ SS455 Mortar Mix is available in 1-gallon, 5-gallon, and 55-gallon containers.

ADDITION RATE:

	Portland/ Lime	Masonry Cement
Dosage	1.0 qt./bag*	0.5 qt. bag

*Per bag of portland cement; lime not included.
Shelf life – 1 year.

CAUTION:

Avoid contact with skin and eyes. In case of contact with skin, wash affected area with soap and water. In case of contact with eyes, flush eyes with large quantities of water and get medical attention immediately. In case of ingestion, if victim is conscious give two full cups of water. Get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

AccuCast™ SS455 Mortar Mix

Premiere Concrete Admixtures warrants its products to be free from defects in material and manufacture. There are no other warranties by Premiere Concrete Admixtures of any nature whatsoever, expressed or implied. This information is based on data and knowledge believed to be true and accurate at time of publication and is offered as a resource for the users of our products. Premiere Concrete Admixtures assumes no liability in the use of this information and does not warranty the results obtained for any application. Premiere Concrete Admixtures shall not be liable for damages of any sort, the use or results of this product and shall not be responsible for conditions outside its control, including but not limited to, other materials, design, inspection, workmanship and field conditions. No statement, recommendation, or other information is intended to infringe on any patent or copyright held by others.

