

ProFiber®-F

Fibrillated Polypropylene Fiber

DESCRIPTION:

ProFiber®-F is a 100% virgin polypropylene engineered fibrillated fiber designed to provide integral secondary reinforcement for concrete.

ProFiber®-F is chemically inert, it will not degrade in the high alkaline environments of concrete. It can be used in ready-mix concrete and placed using conventional concreting methods. **ProFiber®-F** does not easily segregate from the mix. The addition of **ProFiber®-F** to a concrete mix does not increase water demand.

ProFiber®-F can help to reduce the quantity of surface bleed water thus leading to greater water retention at early stages of hydration.

APPLICATIONS:

- Residential, commercial or industrial flatwork
- Foundations and walls
- Tanks, concrete pipe, burial vaults

ADVANTAGES:

- Reduces permeability of hardened concrete.
- Controls and eliminates plastic shrinkage cracking, restrains crack growth.
- Provides multi-dimensional reinforcement.
- Reduces segregation, minimizes bleed water
- Improves compression ductility and toughness and resistance to spalling.
- Reduces permeability
- Improves impact, shatter and abrasion resistance.

BATCHING:

ProFiber®-F can be added during or after the charging of the mixer. Mix for 4 minutes or 75 revolutions at mixing speed to assure adequate distribution.

NORMAL DOSAGE:

1.5lb/yd³ (900 g/m³)

SPECIFICATIONS/COMPLIANCES:

- Meets ASTM C 1116 Standard specification for fiber reinforced concrete and shotcrete, type III, and meets ANSI / UL263, ASTM E119 for fire resistance
- Complies with applicable portion of the International Conference of Building Officials (ICBO) acceptance criteria AC32

PACKAGING:

ProFiber®-F is packaged in .75 lb (0.34 kg), 1.0 lb (0.45 kg) and 1.5 lb (0.68 kg) water dispersible low tear bags.

COMPATIBILITY:

ProFiber®-F is fully effective and compatible in concrete containing all types of Portland cement, class C and F fly ash, calcium chloride, fibers and approved water-reducing, accelerating and retarding admixtures.

SHELF-LIFE:

3 years

TECHNICAL NOTE:

Please contact your Premiere Concrete Solutions Specialist for a pre-placement to discuss helpful batching, placement, finishing and curing procedures.



ProFiber®-F

Fibrillated Polypropylene Fiber

| <u>Property</u> | <u>Characteristic</u> | <u>ASTM</u> |
|---------------------------------|--------------------------------|--------------|
| Available Cut Length | 0.75 in. (19mm), 1.5 in (38mm) | |
| Denier | 1200 (1050-1350) | ASTM 1577B |
| Elongation | 12-18% | ASTM 2101-91 |
| Fibers per lb. | N/A | |
| Resin Melt Flow Rate, g/10 min, | 3-5 | ASTM D-1238 |
| Density, g/cm ³ | 0.905 | ASTM D-1505 |
| Melting Point, C | 160-170 | ASTM - DSC |
| Young's Modulus, Ksi | 580 | |
| Ignition Point | 1100 deg F | |
| Tensile Strength, psi | 97,000 | ASTM D-3822 |
| Acid & Salt Resistance | High | |
| UV Resistance | Excellent | |
| Alkali Resistance | Excellent | |
| Specific Gravity | 0.91 | |
| Heat Conductivity | Low | |
| Electrical Conductivity | Low | |
| Water Absorption | Nil | |

Premiere Concrete Admixtures warrants its products to be free from defects in material and manufacture. There are no other warranties by Premiere Concrete Admixtures of any nature whatsoever, expressed or implied. This information is based on data and knowledge believed to be true and accurate at time of publication and is offered as a resource for the users of our products. Premiere Concrete Admixtures assumes no liability in the use of this information and does not warranty the results obtained for any application. Premiere Concrete Admixtures shall not be liable for damages of any sort, the use or results of this product and shall not be responsible for conditions outside its control, including but not limited to, other materials, design, inspection, workmanship and field conditions. No statement, recommendation, or other information is intended to infringe on any patent or copyright held by others.

