



## Safety Data Sheet NitroCast® HE

Revision date: January 2, 2020

### Section 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product name:** NitroCast® HE  
**Synonyms:** None  
**Chemical family:** Chloride Water-Reducing and Accelerating Concrete Admixture  
**Producer:** Premiere Concrete Admixtures  
508 Cedar Street  
Pioneer, Ohio 43554  
[www.premiereadmix.com](http://www.premiereadmix.com)

**Telephone:** 419-737-9808 Available during normal business hours

**Emergency:** CHEMTREC 800-424-9300 Available 24 hours

### Section 2. HAZARDS IDENTIFICATION

#### GHS Hazard Classification and Label Elements

**WARNING** — Skin corrosion/ irritation (*category 2*)  
**WARNING** — Serious eye damage/ irritation (*category 2A*)  
**WARNING** — Acute toxicity, oral (*category 4*)  
**WARNING** — Acute toxicity, dermal (*category 4*)



#### Hazard Statements

H315 Causes skin irritation  
H319 Causes serious eye irritation  
H302+H312 Harmful if swallowed or in contact with skin

#### Precautionary Statements and Symptoms

P 302 + 352 + 362: IF ON SKIN: Take off contaminated clothing and wash off immediately with plenty of water (see first aid, Section 4).  
P272 + P364: Contaminated work clothing should not be allowed out of the workplace, and wash before re-use.  
P261 Avoid breathing mist, vapor, or spray  
P264 Wash skin thoroughly after handling  
P270 Do not eat, drink, or smoke when using this product.  
P280: Wear protective eye/ face protection, gloves, and clothing (see Section 8).  
P284 In case of inadequate ventilation, wear respiratory protection.  
P313 + P332: If skin irritation or rash occurs, get medical advice/attention.  
P305+315+351+338 If in eyes, rinse continuously for several minutes, remove contact lenses if present and easy to do so, continue rinsing (see first aid Section 4).  
P337+P313 If eye irritation persists, get medical advice/ attention.  
P501: Dispose of unusable contents and the container in accordance with local, state, provincial, and Federal regulations (see Section 13).

### Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Material information:** (Does not include non-GHS regulated ingredients)

Name	CAS No.	Weight %
Calcium chloride	10043-52-4	Less than 33%
Potassium chloride	7447-40-7	Less than 10%
Trihydroxyethylamine	102-71-6	Less than 7%

**\*Note:** The above weight percentages are represented in ranges as estimates. Due to variation among production batches, component percentages may vary.

### Section 4. FIRST AID MEASURES

- Inhalation:** P340: Move exposed persons to fresh air. If the person is not breathing or breathing is irregular, provide artificial respiration or oxygen by trained personnel. Seek medical attention.
- Skin contact:** P361: Quickly remove contaminated clothing and shoes. P321: Wash affected skin with plenty of water and soap. Contaminated work clothing should not be allowed out of the workplace. P361+P364: Wash contaminated clothing before reuse. P302+ P310: Call a physician or poison control center immediately.
- Ingestion:** Do not induce vomiting unless instructed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. P330: If conscious and alert, rinse mouth with water. P301+ P310: Call a physician or poison control center immediately.
- Eye contact:** Check for and remove any contact lenses. Flushing eyes with tepid water lifting upper and lower lids for 15 minutes. Seek medical attention.

### Section 5. FIREFIGHTING MEASURES

**Suitable extinguishing media:** Use an extinguishing agent suitable for the surrounding fire.


**Specific hazards:** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. See Section 10 for hazardous combustion products.

**Special protective equipment for firefighters:** As with any fire, wear self-contained breathing apparatus and full protective gear.

**NFPA rating: HMIS rating:**

<b>Health:</b>	<b>2</b>	<b>2</b>
<b>Flammability:</b>	<b>0</b>	<b>0</b>
<b>Instability/reactivity:</b>	<b>0</b>	<b>0</b>
<b>Other:</b>	<b>N/A</b>	<b>*(PPE)</b>

**\*The customer is responsible for determining the PPE code for this material**



### Section 6. ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Immediately contact emergency personnel. Avoid mist formation. Avoid breathing vapors or mist. Ensure adequate ventilation.
- Large Spill:** Do not let product enter drains. Personnel must have appropriate training, per Occupational Safety and Health Administration (OSHA) 29 CFR 1910.120.

**Methods for Containment and Clean up** | Avoid creating or breathing mist or vapors. Absorb with inert material and keep in a suitable, closed container for disposal. Wear personal protective equipment (Section 8).

## Section 7. HANDLING AND STORAGE

**Handling:** | Keep containers closed when not in use. Avoid formation of mist and aerosols.  
**Storage:** | P403+P233+P405: Store in the original container, locked up, in a well ventilated place, away from incompatible materials, direct sunlight, and away from food or drink. See Section 10. Keep from freezing. Keep container tightly closed until ready for use. Do not reuse the container. Average shelf life: 18 months.

## Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Occupational Exposure Limits:

Name	CAS No.	Exposure Limits TWA <sup>A</sup>		
		ACGIH® TLV®	Federal OSHA PELs	OSHA PELs 1989 <sup>B</sup>
Calcium chloride	10043-52-4	Not Established	Not Established	Not Established
Potassium chloride	7447-40-7	Not Established	Not Established	Not Established
Trihydroxyethylamine	102-71-6	5 mg/m <sup>3</sup>	Not Established	Not Established

All exposure limits listed are 8-hour time weighted average (TWA) — except where noted otherwise.

<sup>A</sup> Time Weighted Average (TWA) is an average exposure over the course of an 8-hour work shift.

<sup>B</sup> Federal OSHA 1989 PELs were vacated but are in use and enforced by many state OSHA plans.

**Engineering measures:** General ventilation is acceptable if exposure to materials in this section does not create symptoms listed in Section 2, or exceed exposure limits in this section. If exposure limits are exceeded, provide local exhaust ventilation according to general industrial hygiene practices.

### PERSONAL PROTECTIVE EQUIPMENT

**Respiratory protection:** P284: When engineering controls are not sufficient to reduce exposure to levels below applicable exposure limits, seek professional advice prior to respirator selection and use.

**Skin and body protection:** Handle with impervious (PVC or rubber) gloves. Choose body protection e.g. impervious apron, sleeves, coveralls, as specified by a PPE assessment and the amount of potential splash created.

**Eye protection:** Safety eyewear, for example safety glasses with side shields and face a shield, should be used when a PPE assessment indicates this is necessary to avoid exposure to liquid splashes, or mists.

**Hygiene measures:** Avoid skin exposure. Wash hands before eating, drinking, smoking, or using toilet facilities.

**Other precautions:** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking, and at the end of the work period.

## Section 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Clear brown liquid  
**Physical state (solid/liquid/gas):** Liquid  
**Substance type (pure/mixture):** Mixture  
**Color:** Brown

<b>Odor:</b>	Musty
<b>Molecular weight:</b>	Not available
<b>pH:</b>	7.0 to 10.0
<b>Boiling point/range (5-95%):</b>	212°F, 100°C
<b>Melting point/range:</b>	32°F, 0°C
<b>Decomposition temperature:</b>	Not available
<b>Specific gravity:</b>	1.30 to 1.35
<b>Vapor density:</b>	Not applicable
<b>Vapor pressure:</b>	Not applicable
<b>Evaporation rate (Butyl acetate= 1):</b>	Not applicable
<b>Flash point, method used:</b>	Not applicable
<b>Water solubility:</b>	100 %
<b>VOC Content:</b>	0 %
<b>Auto-ignition temperature:</b>	Material is not self-igniting
<b>Flammable limits in air — lower (%):</b>	Not applicable
<b>Flammable limits in air — upper (%):</b>	Not applicable

## Section 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Stability:</b>	The material is stable.
<b>Possibly hazardous reactions:</b>	Flammable hydrogen may be generated from contact with metals such as zinc and sodium.
<b>Conditions to avoid:</b>	No specific data
<b>Incompatible Materials:</b>	Strong acids, this product is corrosive to some metals such as brass, ferrous metals, and mild steel. Calcium chloride is attacked by bromine trifluoride.
<b>Hazardous decomposition products:</b>	Formed under fire conditions: hydrogen chloride gas, calcium oxide.
<b>Polymerization:</b>	Will not occur.

## Section 11. TOXICOLOGICAL INFORMATION

**Acute toxicity:** No toxicity data is available for the product as a mixture. The following component data is provided.

### Product information:

Name	CAS No.	Inhalation:	Dermal:	Oral:
Calcium chloride	10043-52-4	Not available	Not available	Acute LD <sub>50</sub> (Rat):2,301 mg/kg
Potassium chloride	7447-40-7	Not available	Not available	Not available
Trihydroxyethylamine	102-71-6	Not available	Acute LD <sub>50</sub> (Rabbit):>2,000 mg/kg	Acute LD <sub>50</sub> (Rat):6,400 mg/kg

**Chronic toxicity:** Ingredients are not listed by the NTP, OSHA, or EPA as carcinogenic. Triethanolamine is identified by the IARC as category 3: unclassifiable as to carcinogenicity in humans.

**Sensitization:** Not known to cause sensitization in humans.

## Section 12. ECOLOGICAL INFORMATION

### Ecotoxicity effects:

Calcium chloride  
 LC<sub>50</sub> (Fish) *Lepomis macrochirus* – 10,650 mg/liter  
 Acute EC<sub>50</sub> (OCED test guideline 202); 48 hours. *Daphnia magna* (water flea) 2,400 mg/liter.

	<u>Trihydroxyethylamine</u> Acute EC <sub>50</sub> ASTM; 48 hours/static. Daphnia 609.88 mg/liter. Chronic NOEC; (no official guidelines) 21 days. Daphnia 16 mg/liter.
<b>Bioaccumulative Potential:</b>	<u>Trihydroxyethylamine</u> Log P <sub>ow</sub> : -2.3; BCF: <3.9; Potential: low.
<b>Persistence and degradability:</b>	<u>Trihydroxyethylamine</u> No official guidelines: readily biodegradable; 100% after 5 days.
<b>Mobility in Soil:</b>	<u>Trihydroxyethylamine</u> : Soil/water partition coefficient (K <sub>oc</sub> ): 10. <u>Calcium chloride</u> : Soil/water partition coefficient (K <sub>oc</sub> ): between 0-50.

### Section 13. DISPOSAL CONSIDERATIONS

**Disposal considerations:** Generation of waste should be avoided or minimized wherever possible. This material and its container must be disposed of in a safe way. P501: Empty containers or liners may retain some product residues. Dispose in accordance with state/ provincial, and local regulations.

### Section 14. TRANSPORT INFORMATION

Please refer to DOT regulation 49 CFR 172.101:

**Transport information:** Not regulated for transport.  
**Hazardous Materials Description:** (DOT and IATA): None.  
**UN/identification no.:** None.  
**Proper shipping name:** None.  
**Hazard class:** None.  
**Packing group:** None.  
**DOT reportable quantity (lbs.):** None.

### Section 15. REGULATORY INFORMATION

**U.S. federal regulatory information:**

**State and community right-to-know regulations:**

*The following component(s) of this material are identified on the regulatory lists below:*

**U.S. TSCA Chemical inventory Section 8(b), AICS (Australia), DSL (Canada):**

Triethanolamine, CAS Number 102-71-6, is listed in TSCA, AICS, and DSL.

**OSHA** — This product is determined to be hazardous as defined in the OSHA Hazard Communications Standard.

**CERCLA** Sections 102a/103 (40 FR 302.4): This product is not classified as hazardous or reportable under this requirement.

Some Components of this product are listed in the following sections of **SARA**:

SARA Title III Section 302 — Not applicable

SARA Title III Section 304 — Not applicable

SARA Title III Section 313 — This product does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels.

SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21)

Acute health hazard: Yes  
Chronic health hazard: No  
Fire hazard: No  
Reactive Hazard: No  
Pressure Hazard: No

**RCRA Regulated Components:** None

**Marine Pollutant:** Not listed

**State Regulations:** Triethanolamine, CAS Number 102-71-6, appears on the following state hazardous substance lists: RI, MN, MA and PA. Check individual state requirements.

### **California Proposition 65 Components**

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

### **INTERNATIONAL REGULATIONS**

**Identification According to EEC Directives:** Not available

### **WHMIS (Canada)**

Not controlled under WHMIS

All ingredients are on the Domestic Substance List (DSL) of Environment Canada

**NOTE:** *User must consult with applicable state and local agencies for special specifics, determinations or compliance obligations regarding this product.*

## **Section 16. OTHER INFORMATION**

The information and recommendations contained herein are based upon tests, data, and information resources believed to be reliable. However, **Premiere Concrete Admixtures (Premiere)** does not guarantee the accuracy or completeness, nor shall any of this information constitute a warranty, representation, or license of any kind, whether expressed or implied, as to the safety of goods, the merchantability of the goods or the fitness of the goods for a particular purpose. Premiere assumes no responsibility for injuries proximately caused by use of the Materials if reasonable safety procedures are not followed as stipulated in this Safety Data Sheet. Additionally, Premiere assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. The buyer assumes the risk in its use of the Material.