

Reclaim-it™

Returned Concrete Treatment

DESCRIPTION:

Reclaim-it™ is a ready-to-use liquid solution manufactured to treat returned concrete to reclaim for future use as fill. **Reclaim-it™** is introduced to the returned concrete in the drum, and reacts to produce a product that can be easily crushed and processed into a usable fill. **Reclaim-it™** provides concrete producers with an environmentally friendly and sustainable solution to addressing returned concrete. For ease of use, **Reclaim-it™** dosage is standard across mix designs.

ADVANTAGES:

- Provides a cost-effective method for producers to reclaim returned concrete for a productive use.
- Eliminates the need to crush old concrete or dispose of old concrete in landfills, saving time and money.
- Can save space at your plant with consistent piles of reclaimed material.
- Reduces expensive disposal costs associated with returned concrete.

COMPATIBILITY:

Reclaim-it™ is compatible with all types of Portland cement, class C and F fly ash, silica fume, GGBFS, fibers, approved air entraining, and water-reducing admixtures.

DOSAGE RATE:

The recommended dosage of **Reclaim-it™** for treatment of returned concrete is ½ gallon (64oz) per cubic yard.

Specific dosage may vary based upon ambient temperatures, concentrations of cementitious material, and desired processing time. Contact your local technical sales representative for recommended dosages and for assistance when using this product with high-strength mix designs.



USAGE

Ribbon up returned concrete to introduce **Reclaim-it™** with 5 gallons of water per yard directly to the mix. Charge for 50 to 70 revolutions, then ribbon out. The following day, use a loader to break up the pile and back-drag any remaining clumps.

STORAGE

Reclaim-it™ may freeze at temperatures below 35°F (2°C). Although freezing does not harm **Reclaim-it™**, precautions should be taken to protect it from freezing. If it should freeze, thaw at 45°F and reconstitute with mechanical agitation. Do Not Use Pressurized Air For Agitation.

PACKAGING:

55-gallon drums, 275-gallon totes, and bulk tank truck

Premiere Concrete Admixtures • P.O. Box 277 • 508 Cedar Street
Pioneer, OH 43554 • (800) 503-3418 • www.premiereadmix.com

Premiere Concrete Admixtures warrants its products to be free from defects in material and manufacture. There are no other warranties by Premiere Concrete Admixtures of any nature whatsoever, expressed or implied. This information is based on data and knowledge believed to be true and accurate at time of publication and is offered as a resource for the users of our products. Premiere Concrete Admixtures assumes no liability in the use of this information and does not warranty the results obtained for any application. Premiere Concrete Admixtures shall not be liable for damages of any sort, the use or results of this product and shall not be responsible for conditions outside its control, including but not limited to, other materials, design, inspection, workmanship and field conditions. No statement, recommendation, or other information is intended to infringe on any patent or copyright held by others.

